

BENCHTOPS & laminate / Care & Maintenance

The surfaces of **polytec**'s Benchtops & laminate are made from a stain-resistant resin. The toughness and high impermeability of this surface means that **polytec**'s Benchtops & laminate should require no more than wiping with a soft cloth, dampened with plain water or a household detergent mix to remove all common household spills.

GENERAL CLEANING

Using a mild household spray wipe down the benchtop with a soft cloth. Dry using a soft cloth so as not to leave any cleaning solutions on the surface.

You may also use Methylated Spirit on a soft cloth, using a circular cleaning motion. Thoroughly clean over the wider area with water and detergent on a damp cloth afterwards to remove any residual Methylated Spirit.

Always ensure that you refer to the recommendations provided by the cleaning product manufacturer before use.

To ensure that your **polytec** warranty will not be void, DO NOT use any of the following on **polytec** Benchtops & laminate: Commercial Cleaning Products, Abrasive Cleaners, Scouring Pads or Abrasive Papers, Solvents, Thinners, Turpentine (Turps), Ammonia, Bleach, Acetone, Easy-Off BAM!, M.E.K. or any other cleaning agents containing organic solvents or the above mentioned products. DO NOT place hot pans, pots or similar hot objects directly on the surface of the product. DO NOT place heavy objects on the product; apply substantial weight to the product including standing, sitting or lying or; apply excessive impact to or mishandle the product, including scraping objects along, throwing objects against or dropping objects on the product's surface.

Please note: **polytec** provide a limited seven (7) year warranty on all benchtop products which ensures against design, workmanship and manufacturing defects. If you detect any problems with your benchtop, **polytec** must be notified within seven (7) years from the date your benchtop was manufactured. Failure to follow the above care instructions may result in damage to your benchtop and void your entitlement to the warranty. **polytec**'s warranty does not cover wear and tear.

For more information refer to the **polytec** Products Limited Warranty Terms & Conditions document.

The protective film on your doors, panels and benchtops must be removed within three months of installation.



Scan or click the QR code for the latest
Care & Maintenance guides or visit:
www.polytec.com.au/technical/#care-and-maintenance

CONTACT

For further information contact:

Australian Panels Pty. Ltd. (ABN 31 003 246 357)

Address 2 Wella Way,
Somersby NSW 2250,
Australia

Telephone 1300 300 547

Fax 1300 320 547